MATERIAL SAFETY DATA SHEET FIXIRA S

Edition 1ⁿ Edition date:23-04-21

SECTION 1: Identification of the substance/Mixture and the company/Undertaking

- 1.1 Product identifier-
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- It is used as coating for textiles
- 1.3 Details of the supplier of the safety data sheet



KARIKI D. SOLE PARTNERSHIP LTD 12 AIGAIOY str, NIKOPOLI 56429, THESSALONIKI, GREECE TEL: +30 2310-683070, FAX: +30 2310-683074

1.4 Emergency telephone number 210 7793777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureSkin irritant category 2Eye irritant category 22.2 Label elements

.

Precaution statement : Warning PHYSICAL HAZARDS:-HEALTH HAZARDS:

H315: Causes skin irritation

H319: Causes serious eye irritation **ENVIRONMENT HAZARDS**: -

PRECAUTION STATEMENTS

P264 Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P332 + P313: If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 : If eye irritation persists: Get medical advice/attention.

POISING CENTER (GREECE):+30 210-7793777

2.3 Other hazards

No further information.

SECTION 2: Composition/Information of ingredients

SUBSTANCE	CLASSIFICATION	CONC.	REACH SUB.	IDENTIFICATION
		%W/W	NUMBER	A: EINECS Nr
				B: CAS Nr
N,N'-(methylenedi-p-	Skin Irrit. 2 H315	20-25		A=231-034-6
phenylene)bis(aziridine-	Eye Irrit. 2 H319			B=7417-99-4
1-carboxamide)				

SECTION 4: First aid measures

4.1 Description of first aid measures:

General Information: Not expected to be a health hazard when used under normal conditions.

Inhalation: Remove to fresh air. If no rapid recovery, go to the nearest hospital for further treatment.

Skin contact: Remove contaminated clothing. Rinse skin immediately with plenty of water for at least 15 minutes, and follow by washing with soap and water, if available. If redness, swelling, pain and / or blisters insist go to the nearest medical facility for additional treatment.

Eye Contact: Flush eye with copious quantities of water. If persistent irritation occurs, seek medical attention.

Ingestion: If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following signs or symptoms with subsequent appear in the next 6 hours, transport to the nearest first-aid station: fever over 101 $^{\circ}$ F (37 $^{\circ}$ C), shortness of breath, chest congestion continuous cough or shortness of breath.

4.2 Most important symptoms and effects, both acute and delayed Not known

4.3 Indication of any immediate medical attention and special treatment needed Not known

SECTION 5: Firefighting measures

Evacuate the fire area of all personnel not belonging to the group of emergency personnel.

5.1 Extinguishing media

Foam, water spray or water fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

If incomplete combustion occurs may develop carbon monoxide which floats and can be reignited on surface water. Vapors are heavier than air, spreads along the ground and be distant ignition. 5.3 Advice for firefighters

Wear full protective clothing and self contained breathing apparatus. Keep adjacent (to the fire) containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Material Safety Data Sheet.

6.2 Environmental precautions

Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example sprays. Take precautionary measures against static discharges. Ensure electrical continuity by bonding and grounding all equipment

6.3 Methods and material for containment and cleaning up

For small liquid spills, transfer by mechanical means to a labeled, sealed container for product recovery or safe disposal. Allow residues to evaporate or soak the residue of an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills, transfer by mechanical means to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak the residue of an appropriate absorbent material and dispose of safely. Remove contaminated waste. Allow residues to evaporate or soak the residue of an appropriate absorbent material and dispose of safely.

6.4 Reference to other sections

See Chapter 13 for information on disposal. Notify authorities if it occurs or is likely to occur any exposure to the general public or the environment. Vapors with air can form an explosive mixture.

SECTION 7: Handling and storage

Avoid breathing of or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this MSDS (Material Safety Data Sheet). Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. Eliminate sources of ignition. Avoid sparks. Ensure electrical continuity by bonding and grounding all equipment. Vapors are heavier than air, spreads along the ground and be distant ignition. Handle and open container with care in a well-ventilated place. Ventilate the workplace so as to not exceed specified occupational exposure limits (OEL). Do not empty the remaining contents into drains.

7.2 Conditions for safe storage, including any incompatibilities

Must be stored in a diked (bunded) area, away from sunlight, ignition sources and other sources of heat. The Bulk storage tanks should be diked (bunded). Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to humans or the environment. Storage Temperature: Ambient.

7.3 Specific end use(s)

Please refer to Chapter 16 or the annexes for the registered uses under Regulation REACH.

SECTION 8: Exposure control/Personal protection

8.1 Control parameters

8.2 Exposure controls

Read in conjunction with Example Report for your specific use contained in the Annex. Do not swallow. If swallowed, contact a doctor immediately. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based

on a risk assessment of local circumstances. Appropriate measures include: Adequate explosionproof ventilation to control airborne concentrations below the guidelines / limits exposure. Eye washes and showers for emergency use. Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers to be sure about.

Eye Protection: Safety goggles (EN 166) goggles splash chemical goggles (chemical).

Hand protection: When the product comes in contact with the hand, the use of gloves approved to relevant standards (eg Europe: EN374, USA F739) made from the following materials may provide suitable chemical protection. Long-term protection: nitrile gloves Incidental contact / Splash protection: PVC gloves (PVC) or neoprene rubber. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Recommended use cosmetic substance restriction of dry skin without scent.

Skin and body protection: Chemical resistant gloves (near / far) boots, and apron. Usually not required skin protection beyond standard issue work clothes.

Respiratory Protection: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with suppliers of respiratory protective equipment. When respirators are air filtration system, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapors [boiling point less than 65 ° C (149 ° F)] that meets the EN14387. When you can not air-filtering respirators (eg airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Methods for Monitoring Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace to ensure compliance with an Occupational Exposure Limit (OEL) and adequacy of exposure controls. For some substances may have biological monitoring. Examples of sources of recommended air monitoring methods are given below or contact supplier. There may be additional national methods.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods, http://www.cdc.gov/niosh/nmam/nmammenu.html. Occupational Safety and Health Administration (OSHA),

USA: Sampling and Analytical Methods, http://www.oshaslc. gov/dts/sltc/methods/toc.html. Health and Safety Executive (HSE),

UK:Methods for the Determination of Hazardous Substances,

http://www.hsl.gov.uk/publications/mdhs.aspx.

Berufsgenossenschaftliches Institut fór Arbeitssicherheit (BIA), Germany

http://www.hvbg.de/d/bia/index.html. L'Institut National de Recherche et de Securitı, (INRS), France http://www.inrs.fr/securite/hygiene_securite_travail.html.

Berufsgenossenschaftliches Institut fór Arbeitssicherheit (BIA), Germany

http://www.hvbg.de/d/bia/index.html. L'Institut National de Recherche et de Securitı, (INRS), France http://www.inrs.fr/securite/hygiene_securite_travail.html.

Measures to control exposure for environmental release (air) of exhaust air containing vapor (the product) must be adhered to local guidelines on emission limits for volatile substances.

SECTION 9: Physical and che	mical properties		
9.1 Information on basic physica	l and chemical properties		
Properties	Results	Unit	Test
Appearance	White liquid		method
Odor	Characteristic		
Odor limit	-		

рН	9_11					
Freezing point	-3	3°				
Initial holling point/holling ragion	-5 >100	°C				
Flash point	>100	°C				
Fugueration rate	>100	J				
Evaporation rate	-					
Fianinability (solid/gas)	-					
Vener recourse	-	Den				
Vapor pressure	-	Bar				
Palative density	-	V cu/l				
Solubility (iog)	1.04-1.10	Kgr/I				
Solubility (les)	Πληρης σε νερο					
Partition coefficient: n-octanol / water	Log Pow 1.4	°C				
Auto-ignition temperature	-	C				
Decomposition temperature	-	2				
Viscosity	<150	mm ² /sec				
Explosion properties	-					
Oxidizing properties	-					
9.2 Other information						
None						
SECTION 10: Stability and reactivity						
10.1 Reactivity						
Stable under normal conditions of use.						
10.2 Chemical stability						
Stable under normal conditions of use.						
10.3 Possibility of hazardous reactions						
Stable under normal conditions of use.						
10.4 Conditions to avoid						
Avoid heat, sparks, open flames and other ignition sources.						
10.5 Incompatible materials:						
Strong oxidising agents.						
10.6 Hazardous decomposition products:						
Thermal decomposition is highly dependent on conditions. During combustion or thermal or						
oxidative degradation of this material will resu	oxidative degradation of this material will result in a complex mixture of airborne solids. liquids					
and gases, including carbon monoxide, carbon dioxide and other organic compounds.						
		-				
SECTION 11: Toxicological information						
11.1 Information on toxicological effects						
Not available						
SECTION 12: Ecological information						
se offort fer Beological Million Matter						
12.1 Toxicity						
Not available						
12.2 Persistence and degradability						
Not available						
12.3 Bioaccumulativa potential						
Not available						

12.4 Mobility in soil
Not available
12.5 Results of PBT and vPvB assessment
The product contains no substances PBT / vPvT according to Regulation (EC) No 1907/2006,
Annex XIII
12.6 Other adverse effects
None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Material Disposal: If possible, recover or recycle (the product). This produces the waste is responsible for determining the toxicity and physical properties of the material produced for determining the appropriate classification and disposal methods of waste in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water.

Disposal of packaging: Drain container thoroughly After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld containers that have not been cleaned. Send them to remanufacturers containers or metal reclaimer.

Local Legislation: Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14: Transport information

14.1 UN Number
Not applicable
14.2 Proper shipping name
Not applicable
14.3 Transport class
Not applicable
14.4 Packing group
Not applicable
14.5 Marine pollutant
Not dangerous for the environment
14.6 Special precaution for user
See Sec.7
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
There will be no bulk material

SECTION 15: Regularity information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Directive 96/82 / EC (Seveso), annex I, part 2: category 8
Regulation 2006/1907 / EC (REACH)
Regulation 2008/1272 / EC (CLP)
Regulation 2009/790 / EC.
15.2 Chemical safety assessment
Not available

SECTION 16: Other information

H362: May cause harm to breast-fed children.
EUH066: Repeated exposure may cause skin dryness or cracking
H410: Very toxic to aquatic life with long lasting effects.
P201: Obtain special instructions before use.
P308 + P313: IF exposed or concerned: Get medical advice/attention.
P260: Do not breathe vapours.
P273: Avoid release to the environment.
P391: Collect spillage.
P501: Dispose of contents/container according to local/national/prefecture/national/international regulations.